



# FTT; THP L/R - electric

<b>Machine-Type:</b>	Tray Washer		<b>Heating:</b>	Electric
<b>Model:</b>	FTT	FTT; THP	<b>Operation:</b>	Left / Right
<b>Usable-Width:</b>	500	<b>Usable-Height:</b>	40	<b>Main-Switch:</b> Built in Machine
<b>Chemical</b>	conduit for chemical supply			Dimension DN50
<b>Exhaust</b>	Volume	Temp.	Rel. Humidity	Pressure
	350 m³/h	18-22°C	90-98%	ca. 0 Pa
<b>Exhaust</b>	Control and Data-Line			Extended-Length
3.7	Equipotential	min. 1x6mm² provided by customer		3m reserve
3.5	Malfunction-Sensor	5x1,5 mm²		STL 3m reserve
3.4	Exhaust	3x1,5 mm²		STL 3m reserve
3.3	Dosage-System	7x1,5 mm²		STL 3m reserve
<b>Exhaust</b>	Voltage	Frequency	Supply	Fuse
	400 V	50 HZ	3-N-PE	3x50 A
				Cross-Section
				5x10 mm²
				Power
				27,0 kW
				EZ
				3m reserve
<b>Water</b>	Consumption	Temp.	Hardness	Conductance
	200 l/h	12 °C	0-3°d (0,5mmol/l)	150-400µS/cm
				80-120µS/cm
				Dimension
				DN50
				Connection
				G3/4" male
				Position in mm
				100mm AFFL
				100mm AFFL
<b>Water-Flow-Pressure provided by customer min. 1,5 bar / 22 psi</b>				
Heat-Radiation (thermal output to the room)				
	washware	5,8 kW	latent	1,3 kW
			sensibel	4,6 kW

**HOBART** GENERAL INFORMATION

**Installation:** All installations should always comply with all national and local codes of practice.

**Exhaust:** A frost-protection flap is recommended if the exhaust air from the machine is exterior ducted.

**Transport:** Minimum measurements of entry doors for machine assembly = outer measurements of largest machine + 300mm in height, + 400mm in width!

**Aeration:** The ventilation and exhaust for the room must be interpreted according to local by-laws

**Heat pump:** Proper working order can only be ensured by room temperature above 18°C.

**Shut-off valves:** The shut-off valves for rinse water, tank filling or demi-rinse are supplied by others.

**Control- and data lines:** We recommend a conduit for control-lines in the area of the electrical connection.

**Washing result:** A spotless cleaning results can be achieved only with low mineral content of the rinse water. We recommend a conductance of about 80µS/cm.

**Floor drain:** Splash floor drains should be installed for general cleaning purpose.

**Steam- connections:** The in-house steam-flow piping must be equipped with condensate drainage prior to the HOBART steam-connection. The in-house condensate piping must be pressure less and able to absorb all HOBART condensate.

**HOBART** GENERAL LEGEND

AW = drain water (CNS)	KW = cold water	ÜOKFF = above finished floor
Dat = dataline	KWw = cold water soft	UK = lower edge
EZ = power line 230V / 400V	LR = conduit Ø	VEW = demineralized water
FD = floor opening	CNS = stainless steel (inox)	WD = wall opening
HW-VL = hot water flow	MK = supply channell	WS = wall slot
HW-RL = hot water return	PE = equipotential conductor	WW = warm water
ND = low pressure steam	STL = control line	WWw = warm water soft
Kond. = condensate	KB = cored hole Ø	

**HOBART** HOBART GmbH - Robert-Bosch-Straße17 - 77656 Offenburg, Germany  
Tel.: +49(0)781.600-0 - Fax.: +49(0)781.600-2319 - www.hobart.de

Index Änderungen / Changes Datum / Date Name

Das Urheberrecht an dieser Zeichnung verbleibt bei der HOBART GmbH. Jede nicht von uns schriftlich genehmigte Benutzung, Verfielfältigung, Überlassung an Dritte ist strafbar und macht schadensersatzpflichtig. This document contains proprietary and confidential data of HOBART GmbH. No disclosure, reproduction or use of any part thereof may be made without written permission of HOBART GmbH.

**HOBART** Angebot  Quotation  
Auftrag  Order

Datum / Date: 2012 / AUGUST  
Gezeichnet / Drawn by: WH  
Geprüft / Checked by: W: Neumaier  
Projectmanager:

Project: TRAY WASHER FTT  
HEATPUMP THP  
ELECTRIC HEATED

Maßstab / Scale: 1:20  
Order-No.:  
Zeichnungsnummer / Drawing-No.: 22 FTT THP - elec. LR