



NOTE:

1. Freshwater supply for rinse: G3/4", 150-600 KPa, $\geq 340L/h$, filling temperature 10-82 °C, must be cold if condenser is fitted;
freshwater supply for fill : G3/4", 150-600 KPa, $\geq 340L/h$, filling temperature 50-60 °C.
2. Tank drain: DIN50, siphon by customer.
3. Electrical connection:

| Model | Voltage | Power | Fuse | Cross section |
|-------------------|---------------|--------|--------|-------------------|
| CCAD-3853-RE-25-V | 380V 50Hz 3N~ | 49.5kW | 86A | 35mm ² |
| CCAD-3853-RE-35-V | 380V 50Hz 3N~ | 55.5kW | 95A | 35mm ² |
| CCAD-3853-RE-45-V | 380V 50Hz 3N~ | 61.5kW | 95A | 35mm ² |
| CCAD-3863-RE-25-V | 380V 60Hz 3N~ | 49.5kW | 86A | 25mm ² |
| CCAD-3863-RE-35-V | 380V 60Hz 3N~ | 55.5kW | 95A | 35mm ² |
| CCAD-3863-RE-45-V | 380V 60Hz 3N~ | 55.5kW | 95A | 35mm ² |
| CCAD-2253-RE-23-V | 220V 50Hz 3~ | 37.5kW | 103.5A | 35mm ² |
| CCAD-2253-RE-22-V | 220V 50Hz 3~ | 31.5kW | 88A | 35mm ² |
| CCAD-2253-RE-20-V | 220V 50Hz 3~ | 19.5kW | 56.5A | 16mm ² |
| CCAD-2253-RE-30-V | 220V 50Hz 3~ | 25.5kW | 72A | 25mm ² |
| CCAD-2263-RE-23-V | 220V 60Hz 3~ | 37.5kW | 103.5A | 35mm ² |
| CCAD-2263-RE-22-V | 220V 60Hz 3~ | 31.5kW | 88A | 35mm ² |
| CCAD-2263-RE-20-V | 220V 60Hz 3~ | 19.5kW | 56.5A | 16mm ² |
| CCAD-2263-RE-30-V | 220V 60Hz 3~ | 25.5kW | 72A | 25mm ² |
| CCAD-2053-RE-20-V | 200V 50Hz 3~ | 19.5kW | 59A | 25mm ² |
| CCAD-2053-RE-30-V | 200V 50Hz 3~ | 25.5kW | 77A | 25mm ² |

WARNING:
Installation should comply with all National and Local codes at practice.

Model:

- CCAD-385(6)3-RE-2(3)(4)5
- CCAD-225(6)3-RE-2(3)3(0)
- CCAD-2053-RE-2(3)3(0)

- 1、 Tank filling connection G $\frac{3}{4}$.(1 will be rinse filling if without booster)
- 1.1、 Rinse filling connection G $\frac{3}{4}$.(1.1 will be tank filling if without booster)
- 2、 Tank drain DIN50
- 3、 Power line inlet
- 4、 Exhaust 600m³/h



4. Exhaust connection: outlet total above 600 m³/h.
5. Must install the main switch to disconnect electrical power to the machine and manual shut off valves for water.
6. All drain and ventilation connections must be made in accordance with National codes.
7. Pipework external of the machine is to be done on site.