



- 150 W/Ws DN 20 100mm above floor
- 150 F/Ws DN 20 100mm above floor
- 150 Electrical connection 2m free end
- 150 Drain DN 70 50mm above floor
- 150 Siphon by customer
- 150 Pipe for later chemie DN 50 50mm above floor
- 150 equipotential conductor min. 1x6mm<sup>2</sup> by site

As continued product improvement is a policy of Hobart, specifications are subject to change without notice

**PLEASE NOTE:**  
 ALL REQUIRED SERVICE OPENINGS (FLOOR/WALL/CEILING) FOR THE WAREWASHING EQUIPMENT (e.g. POWER, WATER, STEAM, extract Air...) ARE HOBART RECOMMENDATIONS (NOT MEASURED)

Installation should comply with all National and Local codes of practice.  
 Attention: If the exhaust from the machine is exterior ducted, protection from freezing by self-closing louvers is recommended. Ductwork should be watertight and non-corrosive.  
 Right to make necessary structural dimensional changes is reserved.  
 Pipework external of the machine is to be done on site.

ELECTRICAL	4	Exhaust connection (with fan) to adapt to extraction system approx. 1200 m <sup>3</sup> /h - 44 °C - 50 % rel.hum. / pressure 40 Pa	
	3.1	Electrical connection : 400 V - 50 Hz - 3 - PE Fuse : 3 * 63 Ampere Cross section : 4 * 16 mm <sup>2</sup>	36,0 KW 220 mm above floor ( Booster)
	3	Electrical connection : 400 V - 50 Hz - 3 - PE Fuse : 3 * 80 Ampere Cross section : 4 * 25 mm <sup>2</sup>	34,0 KW 220 mm above floor ( Motors, Tankheating and Dryer)
	2	Tank drain - Siphon by customer	DN50 100 mm above floor
WATER	1.1	Warm water connection for tank fill - 260 l (recommended hardness 2 -8° Clark, temperature up to 60° C)	DN20 285 mm above floor
	1	Fresh water connection 2-8° Clark -10 °C - 320 l/h Recommended building flowing water pressure to the dishwasher is min. : 1,5 bar	DN15 165 mm above floor
MACHINE TYP: FUX 2-SAPF-2, ASH,D2AT R/L		HEATING electric	MAIN SWITCH: by others
DAS URHEBERRECHT AN DIESER ZEICHNUNG VERBLEIBT BEI DER HOBART CORPORATION ODER EINER IHRER TOCHTERGESELLSCHAFTEN. JEDE NICHT VON UNS SCHRIFTLICH GENEHMIGTE BENÜTZUNG, Vervielfältigung, Überlassung an Dritte ist strafbar und macht Schadensersatzpflichtig. THIS DOCUMENT CONTAINS PROPRIETARY AND CONFIDENTIAL DATA OF HOBART CORPORATION OR ITS SUBSIDIARIES. NO DISCLOSURE, REPRODUCTION OR USE OF ANY PART THEREOF MAY BE MADE WITHOUT WRITTEN PERMISSION OF HOBART.			
INDEX	CHANGE	DATE	NAME
HOBART GMBH ROBERT-BOSCH-STR. 17 / POSTBOX 1620 77656 OFFENBURG, GERMANY TEL. 0781/600-0 TELEFAX 0781/600-2319			
DATE: 15.Aug.05	PROJECT:	REPLACES DRAWING NO.:	<input type="checkbox"/> PLAN
DRAWN BY: B.Hon.	SCALE: 1:20	ORDER-NO.:	<input checked="" type="checkbox"/> QUOTATION
CHECKED:		DRAWING NO.:	<input type="checkbox"/> ORDER
		D-000-	