

# Demand more. Choose Foster

# **RBC20-60**


## **RBC20-60 Roll-In Blast Chiller Cabinet**



### **Temperature**



### **Dimensions (mm)**



#### **Capacity**

60 Chilling (Kg)

#### Features & Benefits

A specially designed Blast Chiller that accepts the 201 Trolley from the Rational Self Cooking Centre. This new model is part of Foster Refrigerator's revolutionary range of Blast Chillers that features breakthrough technology

- High Quality 304 Stainless Steel Exterior Build Quality
- With a simple 'press and start' operation, the RBC 20 60 Blast Chiller is easy to use
- Capable of blast chilling from +70oC to +3oC in 90 minutes
- Features a hard wearing, long life silicon gasket to accommodate high in-going trolley temperatures

<ul> <li>Incorporates Automatic S chill damage</li> </ul>	Surface Protection	n which prevents fro	ost burn and wind	i	
Supplied as Standard	Optional	O Not Availabl	e 🕜 Yes	N No	
External Finish					
304 Stainless Steel		•			
Internal Finish					
304 Stainless Steel		•			
Shelving					
Rational 201 Trolley		Cap	pacity: <b>1</b>		
Doors					
Solid Full		•			
Hinged - Right Hand					
Base Fittings					
150mm Legs		•			
Refrigeration					
Forced Air		•			
Integral					
Remote - less condensing unit		•			
R404a					
Noise DBA		0			
Drain Required?		8			
Electrical Data					

400 Volts			
50Hz			
60Hz	•		
3 Phase			
Watts	0		
Fuse Required	0		
Product Extras			
Door Pull Handle			
Hold Facility			
Temperature Probe			
Infra-Red Data Download	•		
Hardwired Logging System Interface	•		
Foot Notes			

- Requires connection to external drain. 1" BSP Drain outlet
- Chilling Capacity 60 KG. Chilling capacity 90'C to 3'C in less than 90 minutes within specifications. Entry temperature of up to 90'C for chilling. Freezing capacity from + 70'C to -18'C in less than 240 minutes within specifications
- Maximum Ambient 43'C. Twin Compressor condensing unit housed and dressed for specific application for the RBC 20-60 R
- Dimensions: For ventilation and service access ensure that 400mm minimum clearance is allowed above the RBC 20-60
- Condensing Units: For condensing units, glycol cooling and alternative voltage availability please contact the Foster Sales Team

#### **Contact**

### **Foster Refrigerator**

Oldmedow Road King's Lynn Norfolk PE30 4JU United Kingdom

Telephone: **0843 216 8800** Facsimile: **0843 216 4700** 





**GUARANTEEING YOU THE GREENEST REFRIGERATION AVAILABLE**