

**HOBART**


**WAREWASHING**  
UTENSIL WASHER **UP**



## PREMAX UP



The only utensil washer with a lateral wash system. Compared to other models, this enables the **PREMAX UP** to offer triple the capacity in the same space. Innovative and efficient cleaning systems ensure a perfect wash result with significantly less manual pre-washing.



### CONNECTIONS

① Drain hose	1,800 mm   ID20 / OD25
② Supply hose	2,000 mm   R 3/4"
Required flow rate	5 l/min
Flow pressure	0.5 - 10 bar
Max. supply water temperature	60 °C
③ Power cord	2,000 mm

Supply hose for

④ Detergent	2,500 mm
⑤ Rinse aid	2,500 mm

### TECHNICAL DATA

Cycle times*	120 / 240 / 280 sec. and special cycles
Water consumption	8 l/rack
Tank capacity	80 l
Tank heating	3.3 kW
Power supply	400 / 50 / 3N

### BOOSTER LOADING

Standard	15.3 kW
Alternative	9.1 kW

### TOTAL LOADING

Standard	18.5 kW   3 x 32 A
Alternative	15.5 kW   3 x 25 A
Wash pump	2.9 kW   1,150 l/min
Rack size	600 x 760 mm
Loading height	860 mm
Noise level	66 dB (A)
Weight (gross / net)	232 / 212 kg

\* Thermostop guarantees required temperatures with cold water connection, the actual cycle times extend accordingly.

## PRODUCT ADVANTAGES

- **Extra capacity by side wash system:** capacity up to 6 GN-trays 1/1 or 4 EN2 container
- **Detergent direct spraying system:** system soaks the wash ware following the detergent pre-washing cycle and softens even the most severely encrusted food residues
- **VISIOTRONIC control:** single button control with remaining time indicator together with text and graphic display
- **SENSO-ACTIVE resource management:** constantly measures the quality of the wash water and keeps the amount of rinsing needed in each rinse cycle to the minimum in order to guarantee a fully hygienic wash result
- **POWER wash:** high-pressure washing to wash heavily soiled wash items
- **CLIP-IN wash and rinse arms:** wash and rinse arms can be removed with one hand and without any tools
- **USB-interface:** comfortable download of operational data in form of a protocol via USB
- **GENIUS-X<sup>2</sup> fine filter system:** advanced filter system with pre-wash function reduces detergent consumption up to 35 %
- **ROTOR-X wash system:** separate rotating upper and lower 4-spoke wash arms deliver dynamic wash power
- **VAPOSTOP (optional):** prevents vapour to escape from machine when door is opened
- The optional **drain heat recovery** transfers heat from hot drain water to the fresh-water supply, saving up to 7.4 kW
- The optional **exhaust heat recovery** uses steam to heat fresh feed water and reduces the amount of power needed, saving up to 4.5 kW
- **Loading height:** above-average loading height of 860 mm
- **Intelligent energy management:** the available energy is used continuously. Thus, at a low total loading value the heating time gets reduced
- **VAPO-ACTIVE steam washing:** significantly less manual pre-cleaning and second runs by intensive wash cycles with steam injection
- **Interlocked strainer:** prevents operation without tank strainer
- **EASY-CLEAN concept:** blue markings in the machine help the operator to identify the components which require cleaning
- **Hygiene programme:** for removal of calcium carbonate and other deposits from wash chamber